

Back

?

Certification	Certifier	Applicant : ADM	Equipment Class : Level 3 -	Description
No : ESV150157	: ESV	Instrument	Power Supply or Charger -	: LED Driver
		Engineering	Power Supply	
Certified	Expiry Date	Standard: 61347.2.13:2013 with AS/NZS 61347.1:2002		
Date: 3/12/2015	: 3/12/2020			
Certification Conditions:				

Profiles

Model	Trade Name	Profile			
HBG-100-24ADM	Meanwell	Inputs	100-240V, 1.1A, a.c., 50-60Hz, IP65	Outputs	25V max, 4A, d.c.
Comments					
HBG-100-24ADM, HBG-100-24BADM	Meanwell	Inputs	100-240V, 1.1A, a.c., 50-60Hz, IP67	Outputs	25V max, 4A, d.c.
Comments					
HBG-100-36ADM	Meanwell	Inputs	100-240V, 1.1A, a.c., 50-60Hz, IP65	Outputs	37V max, 2.7A, d.c.
Comments					
HBG-100-36ADM, HBG-	Meanwell	Inputs	100-240V, 1.1A, a.c., 50-60Hz, IP67	Outputs	37V max, 2.7A, d.c.

100-
36BADM**Comments**HBG-
100-
48AADM

Meanwell

Inputs100-240V, 1.1A, a.c.,
50-60Hz, IP65**Outputs**

49V max, 2A, d.c.

CommentsHBG-
100-
48ADM,
HBG-
100-
48BADM

Meanwell

Inputs100-240V, 1.1A, a.c.,
50-60Hz, IP67**Outputs**

49V max, 2A, d.c.

CommentsHBG-
100-
60AADM

Meanwell

Inputs100-240V, 1.1A, a.c.,
50-60Hz, IP65**Outputs**

62V max, 1.6A, d.c.

CommentsHBG-
100-
60ADM,
HBG-
100-
60BADM

Meanwell

Inputs100-240V, 1.1A, a.c.,
50-60Hz, IP67**Outputs**

62V max, 1.6A, d.c.

CommentsHBG-
160-
24AADM

Meanwell

Inputs100-240V, 1.7A, a.c.,
50-60Hz, IP65**Outputs**

24V max, 6.5A, d.c.

CommentsHBG-
160-
24ADM,
HBG-
160-
BADM

Meanwell

Inputs100-240V, 1.7A, a.c.,
50-60Hz, IP67**Outputs**

36V max, 6.5A, d.c.

Comments

HBG-

Meanwell

Inputs

100-240V, 1.7A, a.c.,

Outputs

36V max, 4.4A, d.c.

160-
36AADM

50-60Hz, IP65

Comments

HBG- 160- 36ADM, HBG- 160- 36BADM	Meanwell	Inputs	100-240V, 1.7A, a.c., 50-60Hz, IP67	Outputs	36V max, 4.4A, d.c.
--	----------	---------------	--	----------------	---------------------

Comments

HBG- 160- 48AADM	Meanwell	Inputs	100-240V, 1.7A, a.c., 50-60Hz, IP65	Outputs	48V max, 3.3A, d.c.
------------------------	----------	---------------	--	----------------	---------------------

Comments

HBG- 160- 48ADM, HBG- 160- 48BADM	Meanwell	Inputs	100-240V, 1.7A, a.c., 50-60Hz, IP67	Outputs	48V max, 3.3A, d.c.
--	----------	---------------	--	----------------	---------------------

Comments

HBG- 160- 60AADM	Meanwell	Inputs	100-240V, 1.7A, a.c., 50-60Hz, IP65	Outputs	60V max, 2.6A, d.c.
------------------------	----------	---------------	--	----------------	---------------------

Comments

HBG- 160- 60ADM, HBG- 160- BADM	Meanwell	Inputs	100-240V, 1.7A, a.c., 50-60Hz, IP67	Outputs	60V max, 2.6A, d.c.
--	----------	---------------	--	----------------	---------------------

Comments

HBG- 240- 24AADM	Meanwell	Inputs	100-240V, 2.5A, a.c., 50-60Hz, IP65	Outputs	25V max, 10A, d.c.
------------------------	----------	---------------	--	----------------	--------------------

Comments

HBG-	Meanwell	Inputs	100-240V, 2.5A, a.c.,	Outputs	25V max, 10A, d.c.
------	----------	---------------	-----------------------	----------------	--------------------

240- 24ADM, HBG- 240- 24BADM			50-60Hz, IP67		
Comments					
HBG- 240- 36AADM	Meanwell	Inputs	100-240V, 2.5A, a.c., 50-60Hz, IP65	Outputs	37V max, 6.7A, d.c.
Comments					
HBG- 240- 36ADM, HBG- 240- 36BADM	Meanwell	Inputs	100-240V, 2.5A, a.c., 50-60Hz, IP67	Outputs	37V max, 6.7A, d.c.
Comments					
HBG- 240- 48AADM	Meanwell	Inputs	100-240V, 2.5A, a.c., 50-60Hz, IP65	Outputs	49V max, 5A, d.c.
Comments					
HBG- 240- 48ADM, HBG- 240- 48BADM	Meanwell	Inputs	100-240V, 2.5A, a.c., 50-60Hz, IP67	Outputs	49V max, 5A, d.c.
Comments					
HBG- 240- 60AADM	Meanwell	Inputs	100-240V, 2.5A, a.c., 50-60Hz, IP65	Outputs	62V max, 4A, d.c.
Comments					
HBG- 240- 60ADM, HBG- 240- 60BADM	Meanwell	Inputs	100-240V, 2.5A, a.c., 50-60Hz, IP67	Outputs	62A max, 4A, d.c.

Comments

Version 1.4 Last Updated: 3 July, 2009

© Copyright State of Victoria | [Disclaimer](#) | [Privacy Statement](#) | [State Government of Victoria Home](#) |